

Technical Data Sheet

updated
checked

09.05.2014
26.11.2014

Article-No PES-Fahnenstoff mit "INKTeX+® FL Ausrüstung"

6050KFLBS

JETFLAG-L®, with special heat setting and INKTeX+BS® finishing for inkjet-direct print with different inks, with flame retardant treatment

Material 100 % Polyester

Stock widths app. 183 cm, 310 cm

Finishing rolled on paper cores

Packaging wrapped with foil

Ecology according to Öko-Tex Standard 100, product class IV

Weight

acc. to DIN EN 12127 115.00 [g/m²] +- 3 [%]

Shrinkage

Heat Shrinkage, 195 °C, 90 sec, lengthwise

acc. to AA 25-02 -0.50 [%] +- 1 [%]

Heat Shrinkage, 195 °C, 90 sec, crosswise

acc. to AA 25-02 -0.50 [%] +- 1 [%]

Tearing strength

Maximum tensile elongation, longitudinal direction

acc. to DIN EN ISO 13934-1 45.00 [%] +- 20 [%]

Maximum tensile elongation, cross direction

acc. to DIN EN ISO 13934-1 60.00 [%] +- 20 [%]

Maximum tearing strength, longitudinal direction

acc. to DIN EN ISO 13934-1 min. 360.00 [N/5 cm]

Maximum tearing strength, cross direction

acc. to DIN EN ISO 13934-1 min. 450.00 [N/5 cm]

We do not accept liability for errors. Printing mistakes and changes are reserved.

Georg+Otto Friedrich

EUROPAS GROSSE WIRKWARENPRODUZENTEN

Please pay attention to our general considerations regarding fabrication at www.g-o-friedrich.com

Page 2 / 2

Georg + Otto Friedrich GmbH
Waldstraße 73, 64846 Groß-Zimmern
Telefon: +49 (0) 60 71 492-0
Telefax: +49 (0) 60 71 492-39
www.g-o-friedrich.com

HRB 93510 Darmstadt
UST-ID-Nr.: DE 296663791
Geschäftsführer
Lothar Vorbeck, Peter Vorbeck,
Kai Trippel

Volksbank Odenwald eG
IBAN: DE34 5086 3513 0000 0799 10
BIC: GENODE51MIC
European Money Transfer
Swift: GENOEF

Sparkasse Dieburg
IBAN: DE44 5085 2651 0138 1111 17
BIC: HELADEF1DIE

