

Solvent Anti Curl Roll/POP Up Film (ACB)

A 440gsm banner material that has a smooth scrimless appearance. This product has a grey back for blackout properties. It's no curl appearance and scratch resistance may eliminate the need to overlaminate.

TECHNICAL SPECIFICATION

	Value	T Method
Weight	440gsm	
Tear Strength	1182x1173N/5cm	

AVAILABLE SIZES

914mm	(36")	x 50m	3" Core
1372mm	(54")	x 50m	3" Core

APPLICATIONS AND CHARACTERISTICS

- Smooth scrimless printing surface
- Vibrant image reproduction
- Accepts high DPI ink coverage
- Grey back for block out properties
- For use with Solvent, Eco Solvent and UV Curable inks
- 3 part construction of PVC/Polyester/PVC
- Excellent no curl properties

PRINTER COMPATIBILITY CHART

Printer and driver settings may need careful calibration to ensure optimum performance. Ink loads need to be calibrated for the combination of the printer and ink being used.

MANUFACTURER

MODEL

INKS

Whilst each and every one of our products is rigorously tested across all leading printers and with every major manufactured ink, it is always advisable to consult with your Papergraphics' account handler to optimise media performance and to make sure that you get the best results every time.

APPLICATION NOTES

The minimum application temperature is +5°C. The service temperature range is -20°C to +70°C.

STORAGE AND TRANSPORT

The ideal storage conditions for this product are 35-65% relative humidity with temperatures of +10°C to +30°C. We recommend that you always keep this product in its original packaging.